

HEADLAMP HANDSFREE LIGHTING

Atex approval available





VABO NV Ind. Zone Zolder-Lummen 2109 Boterbosstraat 20 B3550 Heusden-Zolder tel +32(0)13-350.550 fax +32(0)13-350.559 info@vabo.be







The CLASSIC, ACTIVE and PERFORMANCE lines respond to uses from the most basic to the most intensive. Each of these lines corresponds to a use and a need related to light output. The SPECIALIZED line contains headlamps dedicated to specific uses.

CLASSIC HEADLAMPS





ACTIVE HEADLAMPS Bindi Actik 200 Lumen 300 Lumen



PERFORMANCE Reactik Rech – 220 Lumen



Hybrid

Pixa 1

60 Lumen

SPECIALIZED Tacktikka (Core = Rech) 200 Lumen 350 Lumen, Core Rech



Tikkid

Hybrid

Reactik+

20 Lumen



Hybrid

Tikkina

150 Lumen

Actik core

Rech – 350 Lumen



Tikka 200 Lumen



Муо 370 Lumen



Duo S Rech -1100 Lumen



Pixa 3 R Rech – 90 Lumen





VABO NV Ind. Zone Zolder-Lummen 2109 Boterbosstraat 20 B3550 Heusden-Zolder tel +32(0)13-350.550 fax +32(0)13-350.559 info@vabo.be

Hazardous areas	Gas type combusti	ble	Dust type combustible			
	ATEX	HAZLOC	ATEX	HAZLOC		
Permanent or long-term	ZONE 0	Class I Div 1	ZONE 20	Class II Div 1		
Occasional	ZONE 1	Class I Div 1	ZONE 21	Class II Div 1		
Accidental	ZONE 2	Class I Div 2	ZONE 22	Class II Div 2		



Tacktikka +RGB 250 Lumen









PROFESSIONAL – HIGH PERFORMANCE – ATEX Duo Z1 Pack of 5 Duo Z1 Duo Z2 Rech – 360 Lumen

430 Lumen





COMPACT RUGGED HEADLAMPS – ATEX Pixa 2 80 Lumen

Pixa 3 100 Lumen



All information, brandnames and trademarks are properties of their respective owners and is subject to change whithout prior notice. Please visit www.vabo.com



CLASSIC SERIES

E+LITE E02			FL1 STANDARD	(:`x	O 1 TON	Û	FL I STANDARD	FL1 STANDARD
Vabo Ref 11588	Standard Lighting White + White Strobe Red + Red Strobe	15 lm 50 lm 15 lm Red 2 lm 2 lm	6 m 10 m 100m 100m 100 m	12 h 9 h 95 h 15 h 70 h	26 g	2 x CR2032	IPX7	-1 m for 30 minutes
Ultra-compact emergency headla	amp 50 lumens	Ultra-compact a Always ready to White lighting al For emergency s distance Locking on/off s Withstands extra Waterproof to -1	use, can be lows you to situations, t witch desig eme temper	e stored with move arou he powerful ned to preve ratures: -30	n batteries (nd easily in red LED allo ent accident ° C to +60°	lithium CR 2 the dark ows you to l al operation	2032) for be seen f	10 years

TIKKINA E91		LUMENS	FL1 STANDARD	(in	0 1 TON	Û	R 1 STANDARD	PL I STANDARD
Vabo Ref 11963	Standard Lighting White Led	6 lm 100 lm 250 lm	10 m 40 m 60 m	120 h 9 h 2 h	81 g	3 AAA	IPX 4	
Simple, compact headlamp for proximity lighting 250 lumens		Description Compact and lig Easy to use: - three white lig - single button f - HYBRID CONC compatible with - detachable, wa Compatible with kind of helmet, wa Specifications Brightness: 250 Weight: 81 g Beam pattern: ff Energy: Three A (available as acc Battery compatil Certification(s): Watertightness:	hting levels or quick and EPT design the CORE r ashable hea mounting a or to a bicy lumens (AN lood VAA/LR03 ba cessory) bility: alkalin CE	: proximity, d easy lighti : TIKKINA c rechargeable dband accessories cle. NSI/PLATO F atteries (incl ne, lithium c	ng level sele omes with 3 e battery that allow th EL 1) luded) or CC or Ni-MH rec	ection standard b ne lamp to l DRE recharg	batteries a	ed to any



CLASSIC SERIES

TIKKA E93		PLI STANDARD	PL 1 STANDARD	<i>(</i> :``	1 TON	Û	FL1 STANDARD	FLI STANDARD
Vabo Ref 11964 Standard Lighting White Led Red Led Red Strobe		5 lm 100 lm 200 lm 2 lm	10 m 40 m 60 m 5 m 700 m	240 h 60 h 60 h 60 h 400 h	86 g	3 AAA	IPX 4	
Compact headlamp for proximi and some movement 200 lume		Description Compact and lig Long burn time Simple to use, t button with whi easily select the Three lighting n movement and Red lighting pre and stealth, and a group from bl Phosphorescent locating the lam TIKKA is a HYBI comes with thre and is also com rechargeable ba	hanks to its ch to quickle lighting mo nodes: proxi distance vis serves night distance vis serve	single y and ode imity, ion t vision nembers of other useful for rk np: it batteries,	Specificatio Light outpu Weight: 86 Beam patte Energy: Th (included) of (available a Battery con Or the Hyb Certification Watertightr	t: 200 lum g rn: wide ree AAA/LF or CORE re s accessory npatibility: rid Core Ba n(s): CE	to3 batteri chargeabl γ) rechargea tterypack	e battery ble Ni-MH

ZIPKA E93Z		PET STANDARD 0005 LUMENS	FL1 STANDARD	(in	1 TON	Ĺ	FL1 STANDARD	FL1 STANDARD
Vabo Ref 11965	Standard Lighting White Led Red proximity Red Strobe visible at 700 m for 400 h	6 Im 100 Im 300 Im 2 Im	10 m 40 m 65 m 5 m	120 h 9 h 2 h 60 h	66 g	3 AAA	IPX 4	
Simple and ultra-compact headla some movement. 300 lumens	amp for proximity lighting and	Description Ultra-compact a Easy to carry an - self-adjusting r - can be worn o or a tent pole, a Easy to use: - three white lig movement and o - red lighting pre and prevents me from blinding ea - single button f selection of brig - HYBRID CONC comes with three and is also comp rechargeable ba - phosphorescer for locating the	d wear: etractable of n the head, bike frame hting levels distance eserves nigh embers of a ch other or quick and htness or lig EPT design e standard batible with ttery.	cord the wrist : proximity, nt vision group d easy ght color : ZIPKA batteries the CORE is useful	Specificatio Brightness: 1) Weight: 66 Beam patte Energy: Th (included) o (available a Battery com Ni-MH rech Certification Watertightr	300 lumen g ern: flood ree AAA/LR or CORE red s accessory npatibility: a argeable n(s): CE	03 batter chargeabl /) alkaline, li	ies e battery ithium or

All information, brandnames and trademarks are properties of their respective owners and is subject to change whithout prior notice. Please visit www.vabo.com



ACTIVE SERIES

	CTIK CORE 99ABA		PL 1 STANDARD	(i)	0 1 TON	Û	FL 1 STANDARD	PLI STANDARD
Actik Vabo Ref 12247 Actik Core, Rechargeable Vabo Ref 12248	Constant Lighting White and Red Led Strobe	White 6 Im 100 Im 350Im/450core Red 2 Im	White 8 m 45 m 90 m Red 5 m 700 m	Upto 120 h 12 h 2h 60 h 400 h	86 g	3 AAA Or Core recharg. Battery Art 12250	IPX 4	
Compact multi-beam headlamp outdoor activities. 350 lumens	with red lighting, designed for	Description Lightweight, con lumens at 86 g. Two beam patte and several whit meet the need fe lighting in dynar proximity or dist movement - red lighting pre and prevents me from blinding ea Simple to use ar - single button fe selection of brig - HYBRID CONC comes with thre and is also comp rechargeable ba - reflective head visibility - detachable, wa - LOCK function turning it on dur Compatible with that allow the la any kind of helm	rns (flood c e brightnes or high-per nic outdoor ance vision eserves nigh embers of a ch other nd practical or quick and htness or lig EPT design e standard batible with ttery. band for nig ashable hea to avoid ac ing transit mounting a	or mixed) s levels formance activities: and rapid nt vision group d easy ght color : ACTIK batteries the CORE ght dband cidentally or storage accessories ttached to	Weight: 86 Beam patte Energy: Th (included) ((available a Battery cor Ni-MH rech Certification Watertightr	ut 0 lumens e : 450 Lun g ern: flood of ree AAA/LR or CORE rea s accessory npatibility: a largeable n(s): CE	r mixed .03 batter chargeabl /) alkaline, li	e battery ithium or



ACTIVE SERIES

CORE RECH	Vabo Ref 12250		FL1 STANDARD	(: N	0 1 TON	Û	FLI STANDARD	FLI STANDARD
Vabo Ref 12250				Upto 3 h	23 g			
Rechargeable battery compatible	e with Petzl HYBRID headlamps	Description Simple universal port Charging indicat = charging; gree Performs well at Economical and as main power so battery Compatible with ZIPKA, ACTIK, A TACTIKKA, TACT TACTIKKA +RGI Product comes of	or on the b en = batter low tempe sustainable supply or ba all TIKKIN ACTIK CORE TIKKA + an 3 headlamp	attery (red y charged) ratures e solution ack-up A, TIKKA, c, d s	Specificatio Weight: 23 Certificatior Type: batte 1250 mAh Recharge ti	g n(s): CE rie recharg	eable Lith	ium-Ion

MYO E87			PL 1 STANDARD	<i>(</i> :``	0 1 TON	Û		PL 1 STANDARD
Vabo Ref 11981	Constant Lighting	White 60 110 280 370 Programmable 20 Im to 170 Im Reserve mode 3 Im for 50 hrs	White 50 65 105	13 5 50 10 sec	168 g	3 AA	IPX 4	
Powerful multi-beam headlamp intended for endurance-oriented outdoor activities. 370 lumens maximum	THE SO	Powerful, high p in Maximum mo Multi-beam light (proximity lightin CONSTANT LIGH - brightness doe - automatically s STANDARD LIGH Several program the activity Reliable and rug are approximate accidental opera resistant for all-v Comfortable & s Perfect for endu on the head for	de). ing: wide-a ng) to a foc ITING tech s not decre switches to ITING tech mable light ged: - batte ly 70 % the tion when l weather use table in activi	ngle flip len used beam nology for E ase gradual reserve mod nology in Ma ing modes t ery charge in en 90 % dise ight body is e (IP X4) ion: incl. top	s that shifts (long-range iconomic and ly as the bat de when bat aximum moo to adapt ligh ndicator ligh charged - sw in upright p o strap provi	instantly fr vision) d Optimum teries drair teries are r de. t intensity a t: warns w vitches are position - w des add. st	rom a wide modes: hearly spen and burn t hen the ba protected ater and v cability wh	e beam nt time to atteries from veather en needed



PERFORMANCE SERIES

SWIFT RL			FL 1 STANDARD	(in	1 TON	Ô	
Vabo Ref 12642	Reactive Lighting Standard lighting	White 100 lm 300 lm 900 lm 10 lm 200 lm 550 lm	White 35 m 55 m 150 m 12 m 55 m 110 m	10-50 h 5-40 h 2-30h 10 h 5 h 2 h	100 g	2350 mAh Lithium-Ion rechargeable battery (included)	IPX 4
Compact multi-beam headlamp, rechargeable, with REACTIVE LI lumens	ultra-powerful and GHTING technology. 900	REACTIVE LIGH beam pattern, o - visual comfort, performance ligi distance vision - comfortable w construction (Pe - reflective head - Lithium-Ion 23 battery charge i Intuitive and cou - ease of use, w lighting modes, - choice of two l or STANDARD L - LOCK function lock lighting set - five-level gaug	ort and burn ne, greater TING mode ptimizing b, from the t hting for ou ear, from th etzl patent), lband for ni 50 mAh ba ndicator nvenient to ith a single brightness lighting mod IGHTING to avoid ac tings during e for precis be tilted up ashable hea 00 lumens EACTIVE LII flood or min nAh Lithium 6 h :: IPX4 (wea	n time: visual comfr e: the light s attery usage wo beam pa itdoor activit he ergonomi for optimal ght visibility ttery, rechai use: button prov and locking des, selected cidentally tu your activit e monitoring ward for see dband (ANSI-FL1 S GHTING or S xed h-Ion rechar	ort and less ensor autom tterns (flood ies: proximi c adjustable stability dur rgeable via t iding contro d with a long urning it on o y o of the batt eing ahead v TANDARD) STANDARD geable batte	manual operation wi natically adjusts brigh d or mixed) giving hig ty vision, movement e headband with two- ring dynamic activitie the type B micro USB of over all functions: (g press: REACTIVE L1 during transit or stora tery charge level when it is worn arour	ntness and gh- and part s port, with ON/OFF, IGHTING age, or to



PERFORMANCE SERIES

NAO +			PL1 STANDARD	<i>(</i> :``	1 TON	Ĺ	FL1 STANDARD
Vabo Ref 12249	Reactive Lighting Constant Lighting Red Led Reserve mode	White 320 lm 750 lm 120 lm 530 lm 15 lm	White 85 m 140 m 65 m 135 m Visible for 1km	15 h 6h30 8 h 1h30 2 h	185 g	2600 mAh Lithium-Ion rechargeable battery (included)	IPX 4
Ultra-powerful, multi-beam, rech programmable, thanks to the My REACTIVE LIGHTING technolog intensity to user needs. 750 lum	yPetzl Light app. Features y that automatically adapts light tens	for smart phone - access remain - adjust brightn - activate and c - headlamp con - four additional mountaineering - headlamp con - the lamp can Longer burn tin LIGHTING tech - the light sense battery use - depending on self-regulates in Lamp can be us constant lightin Multi-beam ligh beam for long-r Ergonomic butt Red indicator lig LOCK function to Rechargeable 2 - universal char - charge indicat Headlamp is ve - adjustable hea - additional top Belt kit accesso belt to reduce to Technology: R Beam pattern: Recharge time	e and tablet ing burn tim less and burn rreate lightin nes with mul l profiles ava g, trekking, b inects throug still be used ne, visual co nology: or automatic the chosen n one of two sed with COI g over time ting: combir ange vision on, even wit ght on the b to avoid acci 600 mAh Lit ging with m for and blue ry stable on adband is ve strap for teo ry for NAO - he weight w EACTIVE LIC wide, mixed e: 6 h	(free downline any time n time g profiles to lti-activity lig- ailable with backpacking gh Bluetootl without the mfort and n cally adjusts burn time (modes: MA NSTANT LIG nes a wide to th gloves attery, in th dentally tur- thium-Ion ba- icro USB po signal for B the head: cry comforta chnical activ + allows the form on the GHTING or fo	oad at App S osuit the act ghting profile the MyPetzl n® Smart (c app ninimal hand brightness a 6.5 h or 15 h X POWER o GHTING tech peam for pro e rear, to sig ning it on du attery: rt luetooth® S ble (Petzl pa ities rechargeab head, or to h CONSTANT L	e Light app: trail runn an be deactivated) lling thanks to its RE and beam pattern, o n), brightness autom r MAX AUTONOMY nology, which ensur ximity lighting with a nal location uring transit or storage mart activation atent) le battery to be mov keep it warm in wint	ay): ing, ACTIVE ptimizing natically es a focused ge



SPECIALIZED SERIES

TACTIKK/ E93	4	LUMENS	FL1 STANDARD	(in	0 1 TON	Û	R1 STANDARD	PLI STANDARD
Vabo Ref 12246	Constant Lighting White and Red Led	White 6 Im 100 Im 300 Im	White 10 m 40 m 65 m	120 h 9 h 2 h	82 g	3 AAA	IPX 4	
	Red Strobe	Red 2 Im	Red 5 m 700 m	60 h 400 h				
	or hunting and fishing. White or red rision and ensure stealth. 300 lumens	Compact and lig Easy to use: - three white br - red lighting pr - single button f - HYBRID CONC also compatible - detachable, w Available in three	ightness lev eserves nigh for quick and CEPT design with the CC ashable hea	rels for proxi nt vision and d easy selec : TACTIKKA DRE recharg dband	d ensures station of brigh comes with eable batter	ealth ntness or lig three stan	jht color	
Hybrid	PERD 9 100	Brightness: 30 Weight: 82 g Beam pattern: Energy: Three (available as a Battery compa Certification(s) Watertightness	flood AAA/LR03 b ccessory) tibility: alkal : CE	patteries (in line, lithium	cluded) or C or Ni-MH re			ttery

TACTIKK/ E89			PL1 STANDARD	(in	0 1 TON	Û	FL1 STANDARD	FL I STANDARD
Vabo Ref 11294	Constant Lighting White Led and Red, Green Blue Led	White 5 Im 100 Im 250 Im Red/green/ blue 2 Im Red Strobe	White 10 m 45 m 70 m Red/ green/bl 5 m 700 m	260 h 50 h 50 h 60 h 400 h	85 g	3 AAA	IPX 4	
	dlamp ideal for hunting and fishing. ghting to preserve night vision and	Red/green/blue lighting preserves night vision and stealth Very powerful lighting with a maximum of 250 lumens Long burn time Three lighting modes: proximity, movement and distance vision Simple to use, thanks to its single button with which to quickly and easily select the lighting mode TACTIKKA +RGB is a HYBRID headlamp: it comes with three standard batteries and is also compatible with the CORE rechargeable battery Available in three colors, depending on use						
Hybrid CONCEPT	ETZL.	Light output: 2 Weight: 85 g Beam pattern: Energy: Three (available as ac Battery compa Certification(s) Watertightness	mixed AAA/LR03 b ccessory) tibility: rech : CE	argeable Ni	-MH	CORE recha	rgeable ba	attery



ATEX SERIES Rechargeable

E80BHR Vabo Ref 12483	RECH Constant Lighting White Led	70 lm 170 lm	20 m 35 m	23 h	370 g	Lithium-ion	IP67					
		300 lm 140 lm 360 lm	90 m 100 m 115 m	12 h 7 h 17 h		J Lithium-ion IP6 ACCU 2 DUO Z1 (incl.)						
	Reserve mode	10 lm		1h 30								
DUO Z1 is a headlamp with a m modes, making it adaptable to e	aximum 360 lumens of lighting in every situation	BOOST mode that	runs on a rec	chargeable ba	ittery. It is mu	Ilti-beam, and has four	lighting					
 close-range lighting: low-in proximity lighting: mixed b lighting for movement: mix distance vision: highly focu BOOST mode provides term Safety and comfort when trabeams cross, enabling those CONSTANT LIGHTING techn Rechargeable battery: Lithium-Ion battery, 6400 r rechargeable in eight hours energy gauge removable and replaceable ACCU 2 DUO Z1 charger (in Reliability and ergonomics: 	s (available as accessory)	burn time comfortable prox ponent for easily nce wer of 360 lumer e FACE2FACE and e each other with e, ideal for long v	moving aro ns ti-glare func out blinding vork periods	ound tion: autom one anothe		s the light when two	or more					



ATEX SERIES

White L Reserve Powerful multi-beam headlamp that rur lumens The DUO Z2 headlamp provides a powe lighting modes, making it adaptable to a FACE2FACE anti-glare function, the DUC enabling them to work more effectively ATEX zone 2/22 (II 3 GD Ex ic IIB T4 G Battery compatibility: Four alkaline bat Other alkaline, rechargeable, Ni-MH an Four modes, plus BOOST, to adapt lighting to - close-range lighting: low-intensity flood bea - proximity lighting: mixed beam with bright - lighting for movement: mixed beam offers - distance vision: highly focused beam for se - BOOST mode provides temporary access to ATEX zone 2/22 (II 3 GD Ex ic IIB T4 Gc III Safety and comfort when traveling in a grou enabling those using DUO headlamps to face CONSTANT LIGHTING technology: stable lig Reliability and ergonomics: - balanced, thanks to the remote battery pace	DUO Z2 E80AHB			(i)	1 TON	Ô	PLI STANDARD
Powerful multi-beam headlamp that rur lumens The DUO Z2 headlamp provides a power lighting modes, making it adaptable to of FACE2FACE anti-glare function, the DUC enabling them to work more effectively ATEX zone 2/22 (II 3 GD Ex ic IIB T4 G Battery compatibility: Four alkaline bat Other alkaline, rechargeable, Ni-MH an Four modes, plus BOOST, to adapt lighting to - close-range lighting: low-intensity flood be - proximity lighting: mixed beam with bright - lighting for movement: mixed beam for se - BOOST mode provides temporary access to ATEX zone 2/22 (II 3 GD Ex ic IIB T4 GC III Safety and comfort when traveling in a grou enabling those using DUO headlamps to face CONSTANT LIGHTING technology: stable lig Reliability and ergonomics: - balanced, thanks to the remote battery page	nt Lighting ed	50 lm 120 lm 220 lm 180 lm 430 lm	17 m 30 m 80 m 120 m 115 m	15h30 6h45 2h 2h45	360 g	4 AA	IP67
lumens The DUO Z2 headlamp provides a power lighting modes, making it adaptable to of FACE2FACE anti-glare function, the DUC enabling them to work more effectively ATEX zone 2/22 (II 3 GD Ex ic IIB T4 G Battery compatibility: Four alkaline bat Other alkaline, rechargeable, Ni-MH an Four modes, plus BOOST, to adapt lighting to - close-range lighting: low-intensity flood bet - proximity lighting: mixed beam with bright - lighting for movement: mixed beam for se - distance vision: highly focused beam for se - BOOST mode provides temporary access to ATEX zone 2/22 (II 3 GD Ex ic IIB T4 Gc III Safety and comfort when traveling in a grou enabling those using DUO headlamps to face CONSTANT LIGHTING technology: stable lig Reliability and ergonomics: - balanced, thanks to the remote battery page	e mode	10 lm		1h			
lighting modes, making it adaptable to of FACE2FACE anti-glare function, the DUG enabling them to work more effectively ATEX zone 2/22 (II 3 GD Ex ic IIB T4 G Battery compatibility: Four alkaline bat Other alkaline, rechargeable, Ni-MH an Four modes, plus BOOST, to adapt lighting to - close-range lighting: low-intensity flood be - proximity lighting: mixed beam with bright - lighting for movement: mixed beam offers - distance vision: highly focused beam for se - BOOST mode provides temporary access to ATEX zone 2/22 (II 3 GD Ex ic IIB T4 Gc III Safety and comfort when traveling in a grou enabling those using DUO headlamps to face CONSTANT LIGHTING technology: stable lig Reliability and ergonomics: - balanced, thanks to the remote battery page	ns on standard batteri	ies, with FACE2	FACE anti-g	lare functior	n, for use in	ATEX hazardous a	areas. 430
 easy-to-use button, even with gloves electronic locking to avoid accidentally turn- automatically switches to reserve mode wh Rugged: IP 67 (waterproof to -1 meter for 30 minut excellent resistance to falls, to impacts and Specifications Light output: 430 lumens Weight (with batteries): 360 g Technology: CONSTANT LIGHTING Beam pattern: flood, mixed or focused Energy: 4 AA/LR06 batteries (included) Watertightness: IP 67 Headlamp comes with two plates for mounting on VERTEX and All 	O Z2 headlamp allows together. It can be w ic IIIB T135° C Dc) ce ttery brands are comp id lithium batteries an o any work situation: am maximizes burn time ness suited for comforta a focused component for eeing at a distance o maximum power of 43 B T135° C Dc) certified p, thanks to the FACE2F e each other without blir hting over time, ideal for ck worn on the back of the ning it on during transit of the batteries are nearly st tes in fresh water) d to crushing	s those working yorn on VERTEX ertification requ patible with AT re only compat e able proximity visi or easily moving a 30 lumens headlamp for use ACE anti-glare fu nding one anothe or long work perio the head or storage	in a group and ALVEC irements fo TEX use (refible with no on around around an explosive nction: autor ir ds	to face each helmets, th r work in ha fer to Instru on-ATEX use environment natically dims	n other withd nanks to the zardous area ctions for Us	en two or more bear	nother, g plates.

PETZL



ATEX SERIES Rechargeable

DUO S E80CHR		FLI STANDARD	PL 1 STANDARD	(:v	1 TON	Û	FLI STANDARD
Vabo Ref	Constant Lighting White Led Reserve mode	80 lm 180 lm 330 lm 700 lm 450 lm 1100 lm 20 lm	20 m 35 m 70 m 160 m 190 m 200 m	23 h 12 h 30 6 h 3 h 30 4 h 30 45 min	360 g	Lithium-Ion Accu 2 (incl)	IP67
Ultra-powerful, recharge	able multi-beam headlamp, featuri	ng the FACE2FA	CE anti-glar	e function. 1	.100 lumens		
vision. Featuring the FAC blinding one another, to plates. ATEX zone 2/22 (II 3 GE Five modes, plus BOOST, to close-range lighting: low-i proximity lighting: mixed l lighting for movement: mi lighting for rapid moveme distance vision: highly foc BOOST mode provides ter CONSTANT LIGHTING techn Rechargeable battery: Lithium-Ion battery, 3200 rechargeable in 4 hours w energy gauge removable and replaceabl Safety and comfort when w enabling those using DUO F Reliability and ergonomics: balanced, thanks to the re easy-to-use button, even automatically switches to electronic locking to avoid Rugged: IP 67 (waterproof to -1 m	vith quick 110/240 V wall charger (inclu le (available as accessory) vorking in a group, thanks to the FACE2 headlamps to face each other without b emote battery pack worn on the back o	JO S headlamp a can be worn on v certification requ ne table proximity vis for easily moving cipating the terrain 1100 lumens for long work perio ided) FACE anti-glare fu linding one anothe f the head Irained	allows those VERTEX and uirements fo ion around n ods	hatically dims	a group to fa mets, thanks	ace each other with s to the included mo as. In two or more beams	out bunting
Technology: CONSTANT LIC Beam pattern: flood, mixed Energy: Lithium-Ion ACCU 2 Recharge time: 4 h Watertightness: IP 67 Headlamp comes with: - two plates for mounting o and ALVEO helmets - 110/240 V charger	l or focused 2 battery (included)						

PETZ



ATEX SERIES

PIXA 1 ATEX E78 AHB-2			FL1 STANDARD	<i>(</i> :)	0 1 TON	Û		FLI STANDARD		
Vabo Ref 11896	Constant Lighting White Led Atex Zone 2 / 22	20 lm 60 lm	10 m 15 m	16 h 3h30	160 g	2 AA	IP67	To -1 m for 30 minutes		
Headlamp suitable for proximity lighting. 60 lumens		Headlamp keeps hands free for work and can be: • worn on the head with the headband • attached to the helmet with a mounting plate (included) • placed on the ground CONSTANT LIGHTING technology ensures brightness that does not gradually decrease as the battery drains Lighting for professionals that is reliable, practical and durable: • two lighting modes (low and high) • proximity lighting mode: wide, comfortable beam for close range work • automatically switches to reserve mode when batteries are almost drained (signaled by blinking light) • rotating knob that is ergonomic, even with gloves • storage position helps protect the headlamp lens and prevents inadvertently turning it on • may be used in explosive environments • excellent resistance to falls (2 m), impacts, and crushing (80 kg) • comfortable and washable elastic headband • resistant to chemicals ATEX Zone 2/22 certified headlamp Battery compatibility: rechargeable Ni-MH and lithium								
PIXA 2 ATEX E78 BHB-2			FL1 STANDARD	(:v	0 1 TON	Û	FL 1 STANDARD	FLI STANDARD		
Vabo Ref 11899	Constant Lighting White Led Atex Zone 2 / 22	20 lm 80 lm	25 m 55 m	26 h 3h30	160 g	2 AA	IP67	To -1 m for 30 minutes		
Headlamp suitable for proximity lumens		Headlamp keeps - worn on the he - attached to the - placed on the of CONSTANT LIGH decrease as the Several lighting - low-intensity n uniform flood - high-intensity n component allow Lighting for prof - automatically s (signaled by blin - rotating knob f - storage position turning it on - may be used in - excellent resists - comfortable ar - resistant to che ATEX Zone 2/22 Battery compation	ead with the e helmet wi ground HTING tech battery dra modes adapt mode adapte mode adapte mode adapte switches to n fessionals th switches to hking light) that is ergon n helps pro n explosive cance to fall d washable emicals	e headband th a mounti nology ensu- ins of to each s ed to close- reed to move nove around reserve mo nomic, ever tect the heat environments s (2 m), im e elastic heat eadlamp	ng plate (inc ires brightne ituation: range work: ment: mixed d comfortabl e, practical a de when bat n with gloves adlamp lens adlamp lens adts pacts, and cr idband	ss that doe mixed beam l beam with y ind durable teries are a and preven ushing (80	m with a w h focused e: almost dra	wide, iined		



ATEX SERIES

PIXA 3 ATE E78 CHB-2		PL1 STANDARD	(in	0 1 TON	Û	FL1 STANDARD	FL1 STANDARD	
Vabo Ref 11897	Constant Lighting White Led Atex Zone 2 / 22	20 lm 60 lm 100 lm Reserve 10 lm	15 m 45 m 90 m	26 h 6h30 3h30 ^{13 h}	160 g	2 AA	IP67	To -1 meter for 30 minutes
Headlamp for proximity lighting vision. 100 lumens		 Headlamp keeps hands free for work and can be: worn on the head with the headband attached to the helmet with a mounting plate (included) placed on the ground CONSTANT LIGHTING technology ensures brightness that does not gradual decrease as the battery drains Several lighting modes adapt to each situation: a mode adapted for close range work: wide, uniform beam a mode adapted for movement: mixed beam with focused component allouser to move around comfortably a mode adapted for long-range vision: focused beam Lighting for professionals that is reliable, practical and durable: automatically switches to reserve mode when batteries are almost drained (signaled by blinking light and red indicator) rotating knob that is ergonomic, even with gloves storage position helps protect the headlamp lens and prevents inadverten turning it on may be used in explosive environments excellent resistance to falls (2 m), impacts, and crushing (80 kg) comfortable and washable elastic headband resistant to chemicals 						allows
PIXA 3R AT	TEX	FL1 STANDARD	FL1 STANDARD	<i>(</i> :	0	ŕ	FL1 STANDARD	FL 1 STANDARD

E78 CHR-2	Recharg.			<i>(</i> :``i	1 TON		<u>III</u>	00m
Vabo Ref 11858	Constant Lighting White Led Rechargeable Atex Zone 2 / 22 certified headlamp	Dimmable 20 lm 55 lm 90 lm 20 lm	Wide/Mix/Focus 15/ - / - - / 45 / 90 25 / 55 / 90 15 / 30 / 50	11 h 30 5h/3h30 3/3h30 11h30	145 g	recharge able Lithium- Ion Polymer battery, 930 mAh	IP67	To -1 m for 30 minutes
Rechargeable headlamp for frequelighting, movement and long-rand	 worn on t attached placed or For frequer quick charged brightness modes ada for close radio component Burn time rapidly turr MAX AUTO 	keeps hands free the head with the to the helmet with the ground ht use, with integ ging dock (3 hour that dœs not gra pt to each situati inge work(wide, c), long-range vis parameters may hing the knob): - NOMY: burn time r professionals th	e headband th a mounti grated recha rs) /CONST/ idually decri- on: uniform bea ion (focused be used to a STANDARD e prioritized	ng plate (ind argeable Lith ANT LIGHTI ease as the am), movem d beam) adapt lightin b: balance be - MAX POW	ium-Ion pol NG technolo battery drain ent(mixed b g performar etween pow ER: brightno	igy ensur ns/Severa beam with nce to ne er and bu	es al lighting n focused ed (by urn time -	

Charge cradle





Accu Reactik, Reactik+



Accu Duo Z1 Rechargeable battery for Duo Z1 headlamp, usable in Atex



Core Rechargeable battery – compatible with Petzl Hybrid headlamps



Pixa Adapt - for mounting a Pixa Headlamp onto a helmet



Accu Nao+



Accu 2 Rechargebal battery for Duo S headlamp

Kit Adapt For mounting a Tikka type headlamp onto a helmet



Kit Adapt For mounting a Tikka type headlamp onto a helmet



Rechargeable battery for PIXA 3R



FIXATION TACTIKKA is a kit that allows the

user to mount or unmount a TACTIKKA,

Fixation Tacktikka

Rubber Headband for Pixa headlamp

CONSULT OUR CATALOGS

MAG-LITE FLASHLIGHTS

MAG-LED[®] Technology Intelligent Energy Source Management

STREAMLIGHT FLASHLIGHTS

And Atex Series





PELI Lights

Atex series , zone 1 & zone 0 Personal lights Arealighting



ACCULUX

Industrial Flashlights – Led – Atex Approved series





Boterbosstraat 20 B-3550 Heusden-Zolder Belgium Tel 0032 (0)13 350 550 Fax 0032 (0)13 350 559 Email info@vabo.be www.vabo.com